

TECHNICAL DATA SHEET

PRODUCTION NAME: Anti-Block MASTERBATCH

PRODUCT GRADE: UATB 01

General Description

This product contains: Anti-block Agent, resin and some additives. It's suitable for blowing film and injection molding, extrusion. The purpose use, it is help easy to open and separate two layer film

Technical Analysis

Physical Property

Items	Method of experiment	Unit	Standard
Anti-block content		wt %	15
Melt Mass-Flow Rate (190°C/2.16kgs)	ASTM D 1238	g/10 mins	25
Melt Temperature	DSC	°C	110
Bulk density	ASTM D1895	g/cm ³	0.6
Water Content	ASTM D 644	wt %	0.01

Properties:

Appearance (Surface color)	: Transparent
Additives	: Dispersion agent, processing aid
Processing temperature	: 140 – 280°C
Usage rate	: 0.5 -3 %
Pellet Size	: 3x3 (±0.3) mm
Carrier resin	: LLDPE
Compatibility	: LLDPE, LDPE, HDPE, PP
Packing	: 25 kg
Storage	: Keep in house

Caution:

This product information is based on our general experience and does not constitute a specification. Since many factors affect the use of our products, no warranty is given or implied with respect to this information or patent infringement. We do not accept liability for any loss or damage arising from the use of this information. All sales are subject to our Standard Terms and Conditions of Sale.