

TECHNICAL DATA SHEET

PRODUCTION NAME: ADDITIVE MASTERBATCH

PRODUCT GRADE: UAST 01

General Description

This product contains: anti-static agent, resin and some other additives. It's suitable for extrusion, blowing film, injection molding, etc. It will bring for the end product ability to resistance free electric on surface

Technical Analysis

Physical Property

Items	Method of experiment	Unit	Standard
Anti-static Agent		wt %	15
Melt Mass-Flow Rate (190°C/2.16kgs)	ASTM D 1238	g/10 mins	30
Melt Temperature	DSC	°C	110
Bulk density	ASTM D1895	g/cm ³	0.58
Water Content	ASTM D 570	wt %	< 0.15

Properties:

Appearance (Surface color)	: white
Processing temperature	: 140 – 280°C
Uses percent	: 1-15 %
Pellet Size	: 3x3 (±0.3) mm
Carrier resin	: LLDPE
Compatibility	: LLDPE, LDPE, HDPE, PP
Packing	: 25 kgs per PP bag
Storage	: Keep at dry condition

Caution:

This product information is based on our general experience and does not constitute a specification. Since many factors affect the use of our products, no warranty is given or implied with respect to this information or patent infringement. We do not accept liability for any loss or damage arising from the use of this information. All sales are subject to our Standard Terms and Conditions of Sale.